

FS120 DATA SHEET



Typical Physical Properties

Colour:	Grey
Thickness / Hardness:	3, 6, 9, 12 & 18mm / Soft
Density:	28kg/cm ³
Elongation	5
90° Peel Adhesion:	405

Parameter values are not guaranteed and will differ from lot to lot.

Application Guide

Surfaces should be clean before applying. Avoid touching adhesive surface before application. Press firmly to ensure good adhesion.

Typical Applications

Automotive gaskets and seals, refrigeration, air conditioning, cushioning applications, draught excluder.

NB: Product is not recommended for water seals.

FS120 Is an open cell polyurethane foam with an aggressive acrylic adhesive

- Maintains a light and dust seal at a minimum 50% compression.
- Remains flexible at a wide range of operation temperatures.
- Dimensionally stable. Will not ooze, run or drip.
- Easily removable liner minimises stretching during installation.
- Good temperature resistance.

Disclaimer All figures shown above represent typical test results in laboratory conditions, and are given without guarantee since the conditions of use are beyond the control of our company. Width and thickness tolerances +/- 20%. It is the customer's responsibility to satisfy themselves that the product is fit for the purpose for which they intend to use it and that the actual conditions of use are suitable.

Excelpac Converting Pty Ltd

ABN: 31 125 089 830

3-4/11 McLellan St Bayswater 3153 Victoria

Tel: 03 9762 9980 Fax: 03 9761 2044

Email: sales@excelpac.com.au